DE600/110 Solids HANDLING





FLOW	HEAD	SPEED	EFFICIENCY
@ BEP	@ BEP	@ BEP	@ BEP
597 m³/hr 2629 usgpm	110 mtrs 361 '	1800 rpm	72%

AT A GLANCE		
Suction Size	200 mm	8 "
Discharge Size	150 mm	6 "
Solids Handling	76 mm	3 "
Max Flow	816 m³/hr	3593 uspgm
Max Head	149 m	489 '
Max Speed	1800 rpm	

DIESEL ENGINE SPECIFICATION		CHOOSE DIESEL
Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	75 ltrs/hr	19.80 usgph
Rated Power @ BEP	249 kW	334 hp
Model	Scania DC13	
Emissions	EU Stage V	
Max Power	331 kW	444 hp

ELECTRIC MOTOR SPECIFICATION		CHOOSE ELECTRIC
Model	WEG / ABB 415V 3 phase 60Hz	
Standard	IEC3	
Rated Power	300 kW	402 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	355 M	

FEATURES & BENEFITS		
Auto Start/Stop	Spark Arrestor	
UK Manufactured	RIGSAFE Shutdown Valve	
Indefinite Dry-Run capabilities		
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime		



To empty an Olympic Swimming Pool (2,500,000 litres) at Max Flow (816 m3/hr)



NET WEIGHT 4100 kgs 9040 lbs

 $L \times W \times H$ 4.25 × 1.60 × 2.20 mtr 167 × 63 × 87

PUMP SPECIFICATION		
Model	CRP150NHTC495	
Priming System	Type: Cornell liquid tolerant diaphragm vacuum pump	
	Air Removal Capability: 50 cfm	
	Priming Chamber: Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover	
	Discharge Check Valve: Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper	
	Run Dry: Indefinite capability	
Impeller	Type: Four Vane, High Head Enclosed Clear Liquids Impeller design providing optimal efficiency	
	Size: 495 mm (19.00 ")	
Volute	Heavy duty GG30 Gray Iron with 125# flanges	
Mechanical Seal	Tungsten Carbide v Silicon Carbide	
Bearing & Shaft	Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft	








ALL DATA IS FOR GUIDANCE PURPOSES ONLY











MARKETS













AROUND YOUR CLOCK, **AROUND YOUR WORLD®**

Anywhere, Anytime... DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

→ +44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM