GI200/150 🗭



EGRATE

FLOW @ BEP 240 m³/hr 1057 usgpm	HEAD @ BEP 144 mtrs 472 '		SPEED @BEP 2200 rp	m	EFFICIENCY @ BEP 68%
AT A GLANCE					
Suction Size		150 mm			6 "
Discharge Size		8	80 mm		3 "
Solids Handling	andling		9 mm		0.75 "
Max Flow		27	'4 m³/hr		1206 usgpm
Max Head		16	68 mtrs		551 '
Max Speed		2200 rpm			
DIESEL ENGINE SPECIFICATION CHOOSE DIESEL					
Fuel Tank Size	Fuel Tank Size		50 Itrs		119 usg
Fuel Burn/hr @	ırn/hr @ BEP 4		2 Itrs/hr		11.10 usgph

		•
Fuel Burn/hr @ BEP 42 ltrs/hr 11.10		11.10 usgph
Rated Power @ BEP	139 kW	186 hp
Model	DEUTZ TCD6.1L4	
Emissions	EU Stage V	
Max Power	180 kW	241 hp

ELECTRIC MOTOR SPECI	FICATION	CHOOSE ELECTRIC
Model	WEG / ABB 415	V 3 phase 50Hz
Standard	IE	C3
Rated Power	185 kW	248 hp
Enclosure	TE	FC
Nominal Speed	1500 rpm	
Frame	3	15

FEATURES & BENEFITS

Auto Start/Stop	
UK Manufactured	

Spark Arrestor
RIGSAFE Shutdown Valve

Indefinite Dry-Run capabilities

Cycloseal - advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime



To empty an Olympic Swimming Pool (2,500,000 litres) at Max Flow (274 m3/hr)



NET WEIGHT 3750 kgs 8267 lbs

 $L \times W \times H$ 3.70 × 1.40 × 2.04 mtr 146 × 55 × 80

PUMP SPECIFICATION		
Model	CRP80MX445	
	Type: Cornell liquid tolerant diaphragm vacuum pump CORNELL	
	Air Removal Capability: 50 cfm	
Priming System	Priming Chamber: Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover	
	Discharge Check Valve: Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper	
	Run Dry: Indefinite capability	
Impeller	Type: Four Vane, CA6NM Enclosed Clear Liquids Impeller design providing long life & optimal efficiency	
	Size: 445 mm (17.51 ")	
Volute	Heavy duty Ductile Iron with 125# flanges	
Mechanical Seal	Tungsten Carbide v Silicon Carbide	
Bearing & Shaft	Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft	







ALL DATA IS FOR GUIDANCE PURPOSES ONLY


🧈 +44(0)1473 833939 | 🔤 SALES@DXBINTEGRATE.COM | 🕨 WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

PERFORMANCE CHART (FOR GUIDANCE ONLY)







MARKETS









🧈 +44(0)1473 833939 | 🔤 SALES@DXBINTEGRATE.COM | 🕨 WWW.DXBINTEGRATE.COM

DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime... DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

GI200/150-0421

AROUND YOUR CLOCK, AROUND YOUR WORLD®