SP4500/15 SOLIDS HANDLING





FLOW	HEAD	SPEED	EFFICIENCY
@ BEP	@ BEP	@ BEP	@ BEP
4480 m³/hr 19720 usgpm	18 mtrs 60 '	600 rpm	

AT A GLANCE		
Suction Size	600 mm	24 "
Discharge Size	600 mm	24 "
Solids Handling	133 mm (min)	5.25 " (min)
Max Flow	5850 m ³ /hr	25760 usgpm
Max Head	26 mtrs	85 '
Max Speed	600 rpm	

DIESEL ENGINE SPECIFI	CHOOSE DIESEL	
Fuel Tank Size	900 ltrs	238 usg
Fuel Burn/hr @ BEP	76 ltrs/hr	20.00 usgph
Rated Power @ BEP	258 kW	346 hp
Model	Scania DC13	
Emissions	EU Stage V	
Max Power	300 kW	402 hp

ELECTRIC MOTOR SPECIFICATION		CHOOSE ELECTRIC	
Model	WEG / ABB 415V 3 phase 50Hz		
Standard	IEC3		
Rated Power	315 kW	422 hp	
Enclosure	TEFC		
Nominal Speed	1500 rpm		
Frame	355		

FEATURES & BENEFITS		
Indefinate Dry-Run capabilities		
Auto Start/Stop		
UK Manufactured		
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime		



To empty an Olympic Swimming Pool (2,500,000 litres) at Max Flow (5850 m³/hr)

DXB8 PUMP & POWER



PUMP SPECIFICATION		
Model	CRP600NNG711	
Priming System	Type: Cornell liquid tolerant diaphragm vacuum pump CORNELL	
	Air Removal Capability: 50 cfm	
	Priming Chamber: Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover	
	Discharge Check Valve: Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper	
	Run Dry: Indefinite capability	
Impeller	Type: Three Vane, Ductile Iron Enclosed Solids Handling Impeller design for large spherical solids pass through whilst providing optimal efficiency	
	Size: 711 mm (27.99 ")	
Volute	Heavy duty Ductile Iron with 125# flanges	
Mechanical Seal	Tungsten Carbide v Silicon Carbide	
Bearing & Shaft	Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft	







ALL DATA IS FOR GUIDANCE PURPOSES ONLY






DXB, AT YOUR SERVICE







AROUND YOUR CLOCK, **AROUND YOUR WORLD®**

Anywhere, Anytime... DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

MARKETS











→ +44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM