



# WASTEWATER



AROUND YOUR WORLD®  
AROUND YOUR CLOCK,  
AROUND YOUR WORLD

# WW250/15



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
249 m <sup>3</sup> /hr 1096 usgpm	16 mtrs 52'	1600 rpm	72%

### AT A GLANCE

Suction Size	150 mm	6"
Discharge Size	150 mm	6"
Solids Handling	76 mm (min)	3" (min)
Max Flow	337 m <sup>3</sup> /hr	1484 usgpm
Max Head	25 mtrs	82'
Max Speed	1600 rpm	

### DIESEL ENGINE SPECIFICATION CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	5 ltrs/hr	1.32 usgph
Rated Power @ BEP	15 kW	20 hp
Model	Deutz D2.2	
Emissions	Stage V	
Max Power	18 kW	24 hp

### ELECTRIC MOTOR SPECIFICATION CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 50Hz	
Standard	IEC3	
Rated Power	18.5 kW	25 hp
Enclosure	TEFC	
Nominal Speed	1500 rpm	
Frame	180 M	

### FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

## 7.42 HOURS

To empty an Olympic Swimming Pool (2,500,000 litres) at Max Flow (337 m<sup>3</sup>/hr)



<b>NET WEIGHT</b>	<b>L x W x H</b>
1380 kgs 3050 lbs	2.10 x 0.95 x 1.75 mtr 82 x 37 x 68"

### PUMP SPECIFICATION

Model	CRP150W256
Priming System	<p><b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump</p> <p><b>Air Removal Capability:</b> 50 cfm</p> <p><b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover</p> <p><b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper</p> <p><b>Run Dry:</b> Indefinite capability</p>
Impeller	<p><b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions</p> <p><b>Size:</b> 256 mm (10.08")</p>
Volute	Heavy duty GG30 Gray Iron with 125# flanges
Mechanical Seal	Tungsten Carbide v Silicon Carbide
Bearing & Shaft	Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft




ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

PERFORMANCE CHART (FOR GUIDANCE ONLY)



DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

MARKETS



# WW250/25



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
274 m <sup>3</sup> /hr 1206 usgpm	24 mtrs 79'	1800 rpm	73%

## AT A GLANCE

Suction Size	150 mm	6"
Discharge Size	150 mm	6"
Solids Handling	76 mm (min)	3" (min)
Max Flow	439 m <sup>3</sup> /hr	1933 usgpm
Max Head	36 mtrs	118'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	7 ltrs/hr	1.85 usgph
Rated Power @ BEP	24 kW	32 hp
Model	Deutz TD2.9	
Emissions	Stage V	
Max Power	36 kW	48 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 50Hz	
Standard	IEC3	
Rated Power	36 kW	48 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	200 L	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**5.70 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (439 m<sup>3</sup>/hr)



DXB3

## NET WEIGHT

1380 kgs  
3050 lbs

## L × W × H

2.10 × 0.95 × 1.75 mtr  
82 × 37 × 68"

## PUMP SPECIFICATION

Model	CRP150NNW256	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 256 mm (10.08")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		




ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

PERFORMANCE CHART (FOR GUIDANCE ONLY)



DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

MARKETS



# WW300/50



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
365 m <sup>3</sup> /hr 1607 usgpm	48 mtrs 157'	1800 rpm	73%

## AT A GLANCE

Suction Size	150 mm	6"
Discharge Size	150 mm	6"
Solids Handling	76 mm	3"
Max Flow	428 m <sup>3</sup> /hr	1884 usgpm
Max Head	68 mtrs	223'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	20 ltrs/hr	5.28 usgph
Rated Power @ BEP	65 kW	87 hp
Model	Deutz TCD 2.9	
Emissions	EU Stage V	
Max Power	55 kW	74 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 50Hz	
Standard	IEC3	
Rated Power	55 kW	74 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	250 M	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**5.84 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (428 m<sup>3</sup>/hr)



DXB3

## NET WEIGHT

2350 kgs  
5180 lbs

## L x W x H

2.85 x 1.20 x 2.00 mtr  
112 x 47 x 78"

## PUMP SPECIFICATION

Model	CRP150NNW356	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 356 mm (14.02")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		






ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

**PERFORMANCE CHART (FOR GUIDANCE ONLY)**



**MARKETS**



**DXB, AT YOUR SERVICE**



**AROUND YOUR CLOCK, AROUND YOUR WORLD®**

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



**WORLD CLASS ECO-FRIENDLY PRODUCTS**

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



**WARRANTY & AFTERCARE**

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



**REAL TIME ASSET CONTROL**

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



**YOUR TRUSTED PARTNER**

Our customers support us, we support them. We're partners!

# WW450/25



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
443 m <sup>3</sup> /hr 1950 usgpm	25 mtrs 82'	1800 rpm	69%

## AT A GLANCE

Suction Size	200 mm	8"
Discharge Size	200 mm	8"
Solids Handling	86 mm	3.40"
Max Flow	597 m <sup>3</sup> /hr	2629 usgpm
Max Head	34 mtrs	111'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	13 ltrs/hr	3.43 usgph
Rated Power @ BEP	41 kW	56 hp
Model	Deutz TD2.9	
Emissions	EU Stage V	
Max Power	55 kW	74 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 60Hz	
Standard	IEC3	
Rated Power	55 kW	74 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	250 S	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**4.20 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (597 m<sup>3</sup>/hr)



DXB3

## NET WEIGHT

2350 kgs  
5180 lbs

## L × W × H

2.85 × 1.20 × 2.00 mtr  
112 × 47 × 79"

## PUMP SPECIFICATION

Model	CRP200NNW280	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 280 mm (11.02")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		




ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®



PERFORMANCE CHART (FOR GUIDANCE ONLY)



MARKETS



DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

# WW500/65



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
634 m <sup>3</sup> /hr 2791 usgpm	61 mtrs 200'	1800 rpm	72%

## AT A GLANCE

Suction Size	200 mm	8"
Discharge Size	200 mm	8"
Solids Handling	76 mm	3.00"
Max Flow	683 m <sup>3</sup> /hr	3000 usgpm
Max Head	90 mtrs	295'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	44 ltrs/hr	11.62 usgph
Rated Power @ BEP	146 kW	196 hp
Model	DEUTZ TCD6.1L4	
Emissions	EU Stage V	
Max Power	180 kW	240 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 60Hz	
Standard	IEC3	
Rated Power	185 kW	248 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	315	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**3.66 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (683 m<sup>3</sup>/hr)



DXB4

## NET WEIGHT

3750 kgs  
8270 lbs

## L × W × H

3.70 × 1.40 × 2.00 mtr  
146 × 55 × 80"

## PUMP SPECIFICATION

Model	CRP150NHWB409	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 409 mm (16.12")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		






ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

PERFORMANCE CHART (FOR GUIDANCE ONLY)



MARKETS



DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

# WW600/70



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
662 m <sup>3</sup> /hr 2915 usgpm	67 mtrs 220'	1700 rpm	73%

## AT A GLANCE

Suction Size	200 mm	8"
Discharge Size	200 mm	8"
Solids Handling	76 mm	3"
Max Flow	709 m <sup>3</sup> /hr	3122 usgpm
Max Head	99 mtrs	325'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	50 ltrs/hr	13.20 usgph
Rated Power @ BEP	167 kW	224 hp
Model	DEUTZ TCD6.1L4	
Emissions	EU Stage V	
Max Power	180 kW	241 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 60Hz	
Standard	IEC3	
Rated Power	185 kW	248 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	315 L	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**3.53 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (709 m<sup>3</sup>/hr)



DXB4

## NET WEIGHT

3750 kgs  
8265 lbs

## L × W × H

3.70 × 1.40 × 2.05 mtr  
146 × 55 × 80"

## PUMP SPECIFICATION

Model	CRP150NHWB445	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 418 mm (16.50")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		






ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

PERFORMANCE CHART (FOR GUIDANCE ONLY)



MARKETS



DXB, AT YOUR SERVICE



AROUND YOUR CLOCK, AROUND YOUR WORLD®

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



WORLD CLASS ECO-FRIENDLY PRODUCTS

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



WARRANTY & AFTERCARE

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



REAL TIME ASSET CONTROL

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



YOUR TRUSTED PARTNER

Our customers support us, we support them. We're partners!

# WW630/40



WARRIOR  
CUTTER



FLOW @ BEP	HEAD @ BEP	SPEED @ BEP	EFFICIENCY @ BEP
627 m <sup>3</sup> /hr 2760 usgpm	41.6 mtrs 136'	1780 rpm	78%

## AT A GLANCE

Suction Size	200 mm	8"
Discharge Size	200 mm	8"
Solids Handling	86 mm (min)	3.40" (min)
Max Flow	795 m <sup>3</sup> /hr	3500 usgpm
Max Head	61 mtrs	200'
Max Speed	1800 rpm	

## DIESEL ENGINE SPECIFICATION

### CHOOSE DIESEL

Fuel Tank Size	450 ltrs	119 usg
Fuel Burn/hr @ BEP	29 ltrs/hr	7.66 usgph
Rated Power @ BEP	91 kW	122 hp
Model	DEUTZ TCD3.6L4	
Emissions	EU Stage V	
Max Power	105 kW	141 hp

## ELECTRIC MOTOR SPECIFICATION

### CHOOSE ELECTRIC

Model	WEG / ABB 415V 3 phase 60Hz	
Standard	IEC3	
Rated Power	110 kW	148 hp
Enclosure	TEFC	
Nominal Speed	1800 rpm	
Frame	280 M	

## FEATURES & BENEFITS

Auto Start/Stop	Spark Arrestor
UK Manufactured	RIGSAFE Shutdown Valve
Indefinite Dry-Run capabilities	
Cycloseal – advanced mechanical seal that extends seal life, reduces seal failures and maximises uptime	

**3.14 HOURS**

To empty an Olympic Swimming Pool  
(2,500,000 litres) at Max Flow (795 m<sup>3</sup>/hr)



## NET WEIGHT

2350 kgs  
5180 lbs

## L × W × H

2.85 × 1.20 × 2.00 mtr  
112 × 47 × 78"

## PUMP SPECIFICATION

Model	CRP200NNW355	
Priming System	<b>Type:</b> Cornell liquid tolerant diaphragm vacuum pump 	<b>Air Removal Capability:</b> 50 cfm  <b>Priming Chamber:</b> Cornell optimised priming chamber design and valve linkage for maximum reliability and zero carryover  <b>Discharge Check Valve:</b> Patented Cornell Non return valve with optional 90 degree discharge and heavy duty flapper  <b>Run Dry:</b> Indefinite capability
	<b>Impeller</b> <b>Type:</b> Two Vane, WasteWarrior unique cutting impeller design for ragging conditions  <b>Size:</b> 355 mm (14.00")	
	<b>Volute</b> Heavy duty GG30 Gray Iron with 125# flanges	
<b>Mechanical Seal</b> Tungsten Carbide v Silicon Carbide		
<b>Bearing &amp; Shaft</b> Heavy-duty bearing housing with dual angular contact bearings on drive end and heavy duty shaft		




ALL DATA IS FOR GUIDANCE PURPOSES ONLY

+44(0)1473 833939 | SALES@DXBINTEGRATE.COM | WWW.DXBINTEGRATE.COM

AROUND YOUR CLOCK, AROUND YOUR WORLD®

**PERFORMANCE CHART (FOR GUIDANCE ONLY)**



**DXB, AT YOUR SERVICE**



**AROUND YOUR CLOCK, AROUND YOUR WORLD®**

Anywhere, Anytime...  
DXB specialise in designing bespoke solutions to your fluid handling challenges.



**WORLD CLASS ECO-FRIENDLY PRODUCTS**

Like you, we care about the environment, which is why our efficient pumpsets use stage 5 emission compliant engines as standard.



**WARRANTY & AFTERCARE**

Our aftermarket team are here to support your business for the life of the pumpset. All products come with market leading warranty period for the absolute peace of mind.



**REAL TIME ASSET CONTROL**

Downtime isn't an option. All our pumpsets can be remotely monitored for ultimate asset control and performance.



**YOUR TRUSTED PARTNER**

Our customers support us, we support them. We're partners!

**MARKETS**

